

Product Sheet

Fairing Compounds



Comparison and Overview

From exterior to deck applications, ALEXSEAL's Fairing Compounds portfolio offers the right solution for every filler challenge. No matter if you need a product with special heat resistance or for cold climates. The following overview shows all the information you need to find the right ALEXSEAL fairing compound for your application.



	Fairing Compound 202	Super Fair 212	Fairing Compound 242	Deckfiller 252
Part-Number	P2094 Fairing Compound 202 Base	P2121 Fairing Compound 212 Base	P2420 Fairing Compound 242 Base	P2520 Deckfiller 252 Base
	C2075 Fairing Compound Converter 202	C2127 Fairing Compound Converter 202	C2427 Fairing Compound Converter 202	C2527 Deckfiller 252 Converter
Mixing Ratio	1:1	1:1	1:1	1:1
Density	Light weight (0.9 kg/l)	Low (0.8 kg/l)	Light weight (0.9 kg/l)	0.5 kg/l
Temperature range	Standard	Good strongest in cold	Best balanced best in heat	NA
Mechanical stability	Most stable	More stable	Most stable	Stable
Final Shore D	70-73	65-67	70-72	50-52
Sanding properties	Good	Best	Medium	Good
Specialty	Best application profile	Flexibility	Best for dark colors	For decks only

Use of ALEXSEAL® Products

Please be note that all ALEXSEAL® products are intended for professional use only and the application process must be carried out by professional users in accordance with the respective material data sheets. The information contained in this data sheet as well as in any ALEXSEAL® material data sheet is based on our level of research and development. Revisal by the user with regard to the intended aim is necessary due to the diverse processing and application possibilities. In case of any doubts regarding the properties and use of our product, please contact your local dealer. Any liability on part of Mankiewicz for faulty applications and / or improper use and any damage arising thereof is expressly excluded whether based on warranty, contract law, torts, negligence, strict liability, misrepresentation or any other area of law except as required by mandatory applicable law.

Mankiewicz Coatings LLC

1200 Charleston Regional Parkway
Charleston, SC 29492, USA
Tel. +1 843 654 7755

📷 [instagram.com/alexsealpaint](https://www.instagram.com/alexsealpaint)
📌 [fb.com/AlexsealYachtCoatings](https://www.facebook.com/AlexsealYachtCoatings)

Mankiewicz Gebr. & Co. (GmbH & Co. KG)

Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
Tel. +49 40 751030

WWW.ALEXSEAL.COM