

Product Sheet

Deckfiller 252



Smooth application for every deck

ALEXSEAL® Deckfiller 252 is a solvent-free, epoxy-based, light-weight filler to be used for fairing decks prior to the installation of teak deck systems. Due to its smooth consistency 252 is very easy to mix and to apply onto the deck surface.

With its **very low density** of 0,5g/cm³ it helps you to save a lot of weight. Thicknesses up to 5mm can be applied in one layer, higher applications are possible in more layers. The material is easy and smooth, slides well and is applicable with a variety of filler tools.

ALEXSEAL's Deckfiller 252 has very little air inclusions and therefore **needs less rework**. It is already sandable after 20 hours of drying time (at approx. 20°C). Due to the smooth texture of the material, sanding with 60-80 grit is very quick and easy.



TRADE NAMES

ALEXSEAL® Deckfiller 252 (Mixing ratio 1:1 by volume)
P2520 ALEXSEAL® Deckfiller 252 Base
C2527 ALEXSEAL® Deckfiller 252 Converter



Your Benefits

- Smooth and easy mixing and application
- Very light weight - density 0,5g/cm³
- Reduction of air pockets
- Easy to sand
- Fast drying

Use of ALEXSEAL® products

Please be note that all ALEXSEAL® products are intended for professional use only and the application process must be carried out by professional users in accordance with the respective material data sheets. The information contained in this data sheet as well as in any ALEXSEAL® material data sheet is based on our level of research and development. Revisal by the user with regard to the intended aim is necessary due to the diverse processing and application possibilities. In case of any doubts regarding the properties and use of our product, please contact your local dealer. Any liability on part of Mankiewicz for faulty applications and / or improper use and any damage arising thereof is expressly excluded whether based on warranty, contract law, torts, negligence, strict liability, misrepresentation or any other area of law except as required by mandatory applicable law.

Mankiewicz Coatings LLC

1200 Charleston Regional Parkway
Charleston, SC 29492, USA
Tel. +1 843 654 7755

📷 [instagram.com/alexsealpaint](https://www.instagram.com/alexsealpaint)
f [fb.com/AlexsealYachtCoatings](https://www.facebook.com/AlexsealYachtCoatings)

Mankiewicz Gebr. & Co.

Georg-Wilhelm-Strasse 189
21107 Hamburg, Germany
Tel. +49 40 751030

WWW.ALEXSEAL.COM