

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

## 1.) Identification of the substance/preparation and of the company/undertaking

### Identification of the substance or preparation

#### Trade name

**ALEXSEAL-Fairing Compound 202 Base P2094**

### Company/undertaking identification

#### Address

Mankiewicz Coatings L.L.C  
831 South 21st Street  
St. Louis, Missouri 63103  
USA

Telephone no. +1 314 783-2110

#### Emergency telephone

CHEMTREC: 800-424-9300 OR 703-527-3887

## 2.) Hazards identification

### Immediate hazards

#### General

WARNING

May cause allergic skin reaction.

May cause skin and eye irritation

#### Potential environmental effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Potential Health Effects

#### Eye

May cause eye irritation.

#### Skin

May cause skin irritation. May cause: Allergic skin reaction

#### Inhalation

No hazard in normal industrial use.

#### Ingestion

May cause vomiting.

#### Cancer

None of the components present in this material at concentrations equal or greater than 0.1% are listed by IARC(Group 1,2A or 2B), NTP, OSHA or ACGIH as a carcinogen.

## 3.) Composition / information on ingredients

### Hazardous ingredients

**REACTION PRODUCT:BISPHENOL A-(EPICHLORHYDRIN),  
EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700)**

|               |            |   |    |        |
|---------------|------------|---|----|--------|
| CAS no.       | 25068-38-6 |   |    |        |
| Concentration | > 30       | < | 50 | %-b.w. |

**REACTION PRODUCT:BISPHENOLF-(EPICHLORHYDRIN), EPOXY RESIN**

|               |            |   |    |        |
|---------------|------------|---|----|--------|
| CAS no.       | 28064-14-4 |   |    |        |
| Concentration | > 5        | < | 10 | %-b.w. |

**1,6-bis(2,3-epoxypropoxy)hexane**

|               |            |   |    |        |
|---------------|------------|---|----|--------|
| CAS no.       | 16096-31-4 |   |    |        |
| Concentration | > 10       | < | 30 | %-b.w. |

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

## 4.) First aid measures

### General information

In all cases of doubt, or when sickness symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

### After inhalation

Remove to fresh air, keep patient warm and at rest. Irregular breathing/no breathing: artificial respiration. If unconscious place in recovery position and seek medical advice.

### After skin contact

Wash skin thoroughly with soap and water or use recognised skin cleaner. Do NOT use solvents or thinners !

### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

### After ingestion

When swallowed seek medical aid immediately and show the physician the packaging or the label of the packaging. Do not induce vomiting.

## 5.) Firefighting measures

### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

### Extinguishing media that must not be used for safety reasons

Full water jet

### Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### Special protective equipment for firefighting

As in any fire, wear self-contained breathing apparatus pressure - demand, MSHA/ NIOSH (approved or equivalent) and full protective gear.

### Other information

Cool endangered containers with water in case of fire. Do not allow run-off from firefighting to enter drains or water courses.

## 6.) Accidental release measures

### Personal precautions

Exclude sources of ignition and ventilate the area. Do not inhale vapours. Refer to protective measures listed in sections 7 and 8.

### Environmental precautions

Do not allow to enter drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### Methods for cleaning up/taking up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in suitable container for disposal. Clean preferably with a detergent; avoid use of solvents.

## 7.) Handling and storage

### Handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Take precautionary

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

measures against electrostatic loading. Refer to protective measures listed in section 8. Comply with the health and safety at work laws.

### **Advice on protection against fire and explosion**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

### **Storage**

#### **Requirements for storage rooms and vessels**

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### **Hints on storage assembly**

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

#### **Further information on storage conditions**

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container in a cool, well-ventilated place.

## **8.) Exposure controls / personal protection**

### **Exposure limit values**

N O N E

### **Exposure controls**

#### **Occupational exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

### **Personal protective equipment**

#### **Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use NIOSH/MSHA approved dust respirator if concentration exceeds recommended exposure levels.

#### **Hand protection**

Glove permeation data does not exist for this material. The following glove(s) should be used for splash protection only.

Appropriate Material                      nitrile

#### **Eye protection**

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

#### **Skin protection**

fire-resistant antistatic protective clothing

#### **General protective and hygiene measures**

Remove soiled or soaked clothing immediately. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation. Do not eat, drink or smoke during work time.

## **9.) Physical and chemical properties**

### **General information**

|       |                        |
|-------|------------------------|
| Form  | liquid                 |
| Color | according product name |
| Odor  | characteristic         |

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
 Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

**Important health, safety and environmental information**

**Changes in physical state**

|          |               |      |     |
|----------|---------------|------|-----|
| Type     | Boiling point |      |     |
| Value    | appr.         | 248  | ° F |
| Pressure | 1013          | mbar |     |

**Flash point**

|        |           |     |     |
|--------|-----------|-----|-----|
| Value  | appr.     | 302 | ° F |
| Method | DIN 53213 |     |     |

**Ignition temperature**

|       |       |     |     |
|-------|-------|-----|-----|
| Value | appr. | 752 | ° F |
|-------|-------|-----|-----|

**Explosion limits**

|                       |    |       |
|-----------------------|----|-------|
| Upper explosion limit | 10 | % vol |
| Lower explosion limit | 1  | % vol |

**Vapor pressure**

|                       |       |     |      |
|-----------------------|-------|-----|------|
| Value                 | appr. | 100 | mbar |
| Reference temperature | 122   | ° F |      |

**Density**

|                       |       |      |            |
|-----------------------|-------|------|------------|
| Value                 | appr. | 9.35 | lbs/gallon |
| Reference temperature | 68    | ° F  |            |

**Viscosity**

|                       |              |     |     |
|-----------------------|--------------|-----|-----|
| Type                  | Efflux time  |     |     |
| Value                 | >            | 150 | sec |
| Method                | DIN cup 4 mm |     |     |
| Reference temperature | 77           | ° F |     |

**Solubility in water**

|         |           |
|---------|-----------|
| Remarks | insoluble |
|---------|-----------|

**10.) Stability and reactivity**

**Conditions to avoid**

Stable under recommended storage and handling conditions(See section 7).

**Materials to avoid**

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Hazardous decomposition products**

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

**11.) Toxicological information**

**Experience in practice**

Possibility of sensitization through skin contact.  
 The product can cause skin and eye irritation.

**12.) Ecological information**

**Other adverse effects**

Ecological data are not available.  
 Do not discharge product unmonitored into the environment.

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

**13.) Disposal considerations**

**Product**

Dispose in accordance with federal, state and local regulations.

**14.) Transport information**

**US DOT**

|                            |  |
|----------------------------|--|
| Class                      | 9  |
| Packaging group            | III  |
| UN/NA number               | 3082   |
| Technical name             | Environmentally hazardous substance, liquid, n.o.s.  |
| Danger releasing substance | REACTION PRODUCT:BISPHENOL A-(EPICHLORHYDRIN),<br>EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) |

**Marine transport IMDG**

|                            |  |
|----------------------------|--|
| Class                      | 9  |
| Packaging group            | III  |
| UN number                  | 3082   |
| Proper shipping name       | Environmentally hazardous substance, liquid, n.o.s.  |
| Danger releasing substance | REACTION PRODUCT:BISPHENOL A-(EPICHLORHYDRIN),<br>EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) |
| EmS                        | F-A,S-F  |
| Label                      | 9  |

**Air transport ICAO/IATA**

|                            |  |
|----------------------------|--|
| Class                      | 9  |
| Packaging group            | III  |
| UN number                  | 3082   |
| Proper shipping name       | Environmentally hazardous substance, liquid, n.o.s.  |
| Danger releasing substance | REACTION PRODUCT:BISPHENOL A-(EPICHLORHYDRIN),<br>EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) |
| Label                      | 9  |

**15.) Regulatory information**

**Regulations**

**US Federal Regulations**

**TSCA (Toxic Substances Control Act)**

All of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements (exempt).

**Clean Water Act (CWA):**

None of the ingredients is listed.

**Clean Air Act:**

None of the ingredients is listed.

**SARA Section 302 (RQ):**

None of the ingredients is listed.

**SARA HAZARD CATEGORY (Section 311/312)**

Acute Health Hazards

**SARA Section 313 INFORMATION:**

None of the ingredients is listed.

**HAPS (Hazardous Air Pollutants):**

None of the ingredients is listed.

**OSHA: Hazardous by definition of Hazard Communication Standard ( 29 CFR 1910.1200)**

Following ingredients are Hazardous by definition of Hazard Communication Standard:

|         |                                    |
|---------|------------------------------------|
| CAS-No. | 25068-38-6; 28064-14-4; 16096-31-4 |
|---------|------------------------------------|

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

Status: 3/6/2008

## State Regulations

### California Proposition 65.

None of the ingredients is listed.

### Pennsylvania HAZARDOUS SUBSTANCE LIST

Following ingredients are listed:

CAS-No. 13463-67-7; 14807-96-6

### New Jersey Worker and Community Right to Know Act.

Following ingredients are listed:

CAS-No. 13463-67-7; 14807-96-6

## US Federal Regulations

### Volatile organic compounds (VOC)

pound/gallon 0

## Other international listings

### IARC

None of the ingredients is listed in group 1, 2A or 2B.

## 16.) Other information

### HMIS Classification

|                |   |
|----------------|---|
| Health         | 2 |
| Flammability : | 1 |
| Reactivity     | 0 |
| PPE            | G |

### NFPA Rating

|             |   |
|-------------|---|
| Health      | 2 |
| Fire Hazard | 1 |
| Reactivity  | 0 |

### Other information

Abbreviations:

ACGIH American Conference of Governmental Hygienics

CAS Chemical Abstracts Service

HAPS Hazardous Air Pollutants

HMIS Hazardous Material Identifikation System

IARC International Agency for Research on Cancer

IDLH Immediate Dangerous to Life and Health

LEL Lower Explosion Limit

NTP National Toxicology Program

OEL Occupational Exposure Limit

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

PPE Personal Protection Equipment

SARA Superfund Amendments and Reauthorization Act

STEL Short-Term Exposure Level (15 minutes)

TWA Time-Weighted Average (8 hours)

UEL Upper Explosion Limit

VOC Volatile Organic Compounds

WEEL Workplace Environmental Exposure Level

### Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183 b, D-21107 Hamburg

Tel.: +49 40 / 41 92 13 00 Fax: +49 40 / 41 92 13 57 e-mail: [umco@umco.de](mailto:umco@umco.de)

# Material Safety Data Sheet



---

Trade name: ALEXSEAL-Fairing Compound 202 Base P2094  
Product no.: 1542098033000 Version: 2.2.0 / USA

---

Status: 3/6/2008

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.