

Premium Polymer Sealer

1. Introduction

ALEXSEAL® Premium Polymer Sealer is a non-abrasive synthetic sealer designed for cleaning and protecting surfaces painted with polyurethane. It is formulated with UV absorbers that will help protect the paint from exposure to the sun and improve the coatings' life expectancy.

ALEXSEAL® Premium Polymer Sealer will remove mild stains and water spots from the surface and leave behind a protective polymer coating which will help seal the surface from the harsh elements of the marine environment.

It is recommended to apply ALEXSEAL® Premium Polymer Sealer every 3 to 4 months to areas that have extreme exposure to sunlight.

2. Range of application

ALEXSEAL® Premium Polymer Sealer is used in combination with ALEXSEAL® Premium Topcoat 501, Metallic Base Coat / Clear Coat System and ALEXSEAL® H/S Clear Coat to achieve a new radiant shine and eliminate weather-related graying.

3. Color

Viscous white liquid

4. Coverage

N.A.

5. Substrate pre-treatment

The surface must be washed with ALEXSEAL® Premium Wash Down Concentrate, rinsed and wiped dry. Please follow the instructions for ALEXSEAL® Premium Wash Down Concentrate.

6. Trade names

Base Material A5010 ALEXSEAL® Premium Polymer Sealer

7. Mixing ratio

Mixing not necessary

8. Application

1. Wash the surface with ALEXSEAL® Premium Wash Down Concentrate, rinse and wipe dry. Follow the instructions for ALEXSEAL® Premium Wash Down Concentrate.

2. Shake ALEXSEAL® Premium Polymer Sealer before applying the sealer on a clean dust free surface. Using a 100% cotton cloth don't apply the sealer with a mechanical device.

3. Allow ALEXSEAL® Premium Polymer Sealer to dry to a haze. Do not allow the material to dry more than 6 hours before removing, as it may be more difficult to remove.

4. Wipe off haze with a 100% clean, cotton cloth or microfiber towel.

5. Multiple coats of ALEXSEAL® Premium Polymer Sealer may be needed to protect water run-off areas.

NOTE:

ALEXSEAL® recommends washing the surface once a week. Use ALEXSEAL® Premium Wash Down Concentrate to minimize removal of the ALEXSEAL® Premium Polymer Sealer.

9. Storage and Shelf Life

Do not freeze.

If the original unopened ALEXSEAL® Premium Polymer Sealer is stored in a cool and dry place the product has a shelf life of 2 years.

10. Packaging

A5010 ALEXSEAL® Premium Polymer Sealer 1 Pt & 1.25 Gal

It is possible to refill the smaller/suitable package (1 Pt) with the larger 1.25 Gal package by opening the cap and filling in the new material.

WARNING: Keep out of reach of children, avoid contact with eyes. If so, flush eyes liberally with water.

FIRST AID: Get medical attention if swallowed.

Professional Use Only

Page 1 of 1

The information contained in this data sheet is based on our level of research and development. Revisal by the user with regard to the intended aim is necessary due to the diverse processing and application possibilities. Any liability on part of Mankiewicz for faulty applications and / or improper use is expressly excluded. revision 2017